

Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD  
Replaces Version: 8 / WORLD

Date created/revised: 03.11.16  
Print date: 15.09.16

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Whittle Waxes

P.O. Box 455 Cooroy. QLD 4563

Telephone no. +61 (0) 1300 326 929 or 07 5471 7963

E-mail address info@whittlewaxes.com.au

### 1.4. Emergency telephone number

Australian +61 13 11 26

## 2. Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226

STOT SE 3 H336

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008 For explanation of abbreviations see section 16.

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

##### Hazard pictograms



##### Signal word

Warning

##### Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

##### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD  
Replaces Version: 8 / WORLD

Date created/revised: 03.11.16  
Print date: 15.09.16

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P309+P315 IF exposed or if you feel unwell: Get immediate medical advice/attention.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

**Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)** contains  
naphtha hydrodesulfurized heavy **Supplemental information**  
EUH066 Repeated exposure may cause skin dryness or cracking.

#### Further supplemental information

Cleaning cloth soaked with the product can self ignite during packing up, therefore dry the cloth on a line or through spreading and dispose of after dry up.

### 2.3. Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB) (if not listed in Section 3).

### 3. Composition/information on ingredients

#### Hazardous ingredients (Regulation (EC) No. 1272/2008) naphtha hydrodesulfurized heavy

CAS No.	64742-48-9
EINECS no.	265-150-3
Registration no.	01-2119463258-33
Concentration	>= 25 < 50 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
Asp. Tox. 1	H304
STOT SE 3	H336

#### alkanes, C11-14-iso-

CAS No.	90622-58-5
Concentration	>= 10 < 25 %

Classification (Regulation (EC) No. 1272/2008)

Asp. Tox. 1	H304
Aquatic Chronic 4	H413

EUH066

#### 2-ethylhexanoic acid zirconium salt

CAS No.	22464-99-9
EINECS no.	245-018-1
Registration no.	01-2119979088-21

Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD  
Replaces Version: 8 / WORLD

Date created/revised: 03.11.16  
Print date: 15.09.16

Concentration >= 1 < 3 %

Classification (Regulation (EC) No. 1272/2008)  
Repr. 2 H361d

**naphtha hydrodesulfurized heavy**

CAS No. 64742-48-9 EINECS no. 265-150-3

Registration no. 01-2119457273-39

Concentration >= 1 < 10 %

Classification (Regulation (EC) No. 1272/2008)  
Asp. Tox. 1 H304  
EUH066

**Further hazardous ingredients**

For explanation of abbreviations see section 16.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) (if not listed in Section 3).

**4. First aid measures**

**4.1. Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical attention. If unconscious place in recovery position and seek medical advice. First aider: Pay attention to self-protection! Remove affected person from danger area, lay him down.

**After inhalation**

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep warm, calm and covered up. In all cases of doubt, or when symptoms persist, seek medical attention.

**After skin contact**

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

**After eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

**After ingestion**

Do not induce vomiting. Take medical treatment.

**4.2. Most important symptoms and effects, both acute and delayed**

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects. The liquid splashed in the eyes may cause irritation and reversible damage.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Hints for the physician / treatment** Treat symptomatically.

Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD

Date created/revised: 03.11.16

Replaces Version: 8 / WORLD

Print date: 15.09.16

## 5. Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

#### Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced.

Exposure to decomposition products may cause a health hazard. Vapours can form an explosive mixture with air.

### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighting

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

#### Other information

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water spray. Standard procedure for chemical fires.

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ensure adequate ventilation. Do not inhale vapours. Do not inhale gases. Do not inhale mist.

### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Clean contaminated floors and objects thoroughly while observing environmental regulations. Clean with detergents. Avoid solvents. Keep in suitable, closed containers for disposal.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

## 7. Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep container tightly closed and dry in a cool, well-ventilated place. Use only with adequate ventilation/personal protection. Ensure adequate ventilation. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. Avoid contact with skin and eyes. Do not breathe

Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD  
Replaces Version: 8 / WORLD

Date created/revised: 03.11.16  
Print date: 15.09.16

vapours or spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

#### Advice on protection against fire and explosion

Vapours may form explosive mixtures with air. Vapours are heavier than air and may spread along floors. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Take measures to prevent the build up of electrostatic charge. Wear shoes with conductive soles. No sparking tools should be used. Fight fire with normal precautions from a reasonable distance. Do not process in the same cabin together with highly flammable material (e.g. CN lacquer) => fire hazard through self ignition! Cleaning cloth soaked with the product can self ignite during packing up, therefore dry the cloth on a line or through spreading and dispose of after dry up.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Provide solvent-resistant and impermeable floor. Store at room temperature in the original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. **Hints on**

#### storage assembly

Keep away from oxidising agents and strongly acid or alkaline materials.

#### Storage class according to the Occupation Safety Ordinance:

Flammable.

#### Further information on storage conditions

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

### 7.3. Specific end use(s)

See exposure scenario, if available.

## 8. Exposure controls/personal protection

### 8.1. Control parameters

#### Other information

-

#### Derived No/Minimal Effect Levels (DNEL/DMEL) naphtha hydrodesulfurized heavy

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	300	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	

Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD  
 Replaces Version: 8 / WORLD

Date created/revised: 03.11.16  
 Print date: 15.09.16

Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1500	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumers	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	300	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumers	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	900	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumers	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	300	mg/kg/d

**2-ethylhexanoic acid zirconium salt**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	32,97	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	

Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD  
 Replaces Version: 8 / WORLD

Date created/revised: 03.11.16  
 Print date: 15.09.16

Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	6,49	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumers	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	4,51	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumers	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	8,13	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumers	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	3,25	mg/kg/d
<b>naphtha hydrodesulfurized heavy</b>		
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	208	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	

Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD  
 Replaces Version: 8 / WORLD

Date created/revised: 03.11.16  
 Print date: 15.09.16

Mode of action	Systemic effects	
Concentration	871	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumers	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	125	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumers	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	125	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumers	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	900	mg/m <sup>3</sup>

**Predicted No Effect Concentration (PNEC)**

**2-ethylhexanoic acid zirconium salt**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,36	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,036	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	6,37	mg/kg
Type of value	PNEC	
Type	saltwater sediment	



Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD  
 Replaces Version: 8 / WORLD

Date created/revised: 03.11.16  
 Print date: 15.09.16

Concentration	0,637	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	1,06	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	71,7	mg/kg

## 8.2. Exposure controls

### Exposure controls

Apply technical measures to comply with the workplace exposure limits. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Recommended Filter type: Respiratory protection mask with combination filter A/P2 **Hand**

### protection

Protective gloves complying with EN 374.

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

### Eye protection

Wear eye glasses with side protection according to EN 166.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Form</b>	liquid
<b>Colour</b>	colourless
<b>Odour</b>	characteristic
<b>Odour threshold</b>	
Remarks <b>pH</b>	no data available
<b>value</b>	
Remarks <b>Melting</b>	no data available
<b>point</b>	

Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD  
 Replaces Version: 8 / WORLD

Date created/revised: 03.11.16  
 Print date: 15.09.16

Remarks	<b>Freezing point</b>	no data available		
Remarks	<b>Initial boiling point and boiling range</b>	no data available		
Value		135	to	217 °C
Remarks	<b>Flash point</b>	no data available		
Value		38		°C
Remarks	<b>Evaporation rate</b>	no data available		
Remarks	<b>Flammability (solid, gas) no data available Upper/lower flammability or explosive limits</b>	no data available		
Remarks	<b>Vapour density</b>	no data available		
Value	<b>Density</b>	0,91		g/cm <sup>3</sup>
Temperature	<b>Solubility in water</b>	20	°C	
Remarks	<b>Solubility(ies)</b>	no data available		
Remarks		no data available		
Remarks	<b>Partition coefficient: n-octanol/water</b>	no data available		
Remarks	<b>Ignition temperature</b>	no data available		
Remarks	<b>Decomposition temperature</b>	no data available		
Remarks	<b>Viscosity</b>	no data available		
Value	<b>Efflux time</b>	52	to	58 s
Temperature		20	°C	
Method		DIN 53211 4 mm		
Remarks	<b>Explosive properties evaluation</b>	no data available		
Remarks	<b>Oxidising properties</b>	no data available		

**9.2. Other information**

**Other information**  
 This information is not available.

Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD  
Replaces Version: 8 / WORLD

Date created/revised: 03.11.16  
Print date: 15.09.16

## 10. Stability and reactivity

### 10.1. Reactivity

No conditions to be specially mentioned.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

### 10.4. Conditions to avoid

Heat, flames and sparks.

#### Decomposition temperature

Remarks no data available

### 10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6. Hazardous decomposition products

Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke. No decomposition if used as prescribed.

## 11. Toxicological information

### 11.1. Information on toxicological effects

#### Acute oral toxicity

Remarks Based on available data, the classification criteria are not met.

#### Acute oral toxicity (Components) naphtha hydrodesulfurized heavy

Species	rat		
LD50 >	5000	alkanes, C11-14-iso-	mg/kg
Species	rat		
LD50	>	5000	mg/kg
Method	OECD 401	naphtha	

#### hydrodesulfurized heavy

Species	rat		
LD50	>	5000	mg/kg

#### Acute dermal toxicity

Remarks Based on available data, the classification criteria are not met.

#### Acute dermal toxicity (Components) naphtha hydrodesulfurized heavy

Species	rat		
---------	-----	--	--

Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD

Date created/revised: 03.11.16

Replaces Version: 8 / WORLD

Print date: 15.09.16

LD50 **alkanes,** 3160 mg/kg

**C11-14-iso-**

Species rabbit

LD50 > 5000 mg/kg

**naphtha hydrodesulfurized heavy**

Species rabbit

LD50 > 3000 mg/kg

**Acute inhalational toxicity**

Remarks Based on available data, the classification criteria are not met.

**Acute inhalative toxicity (Components)**

**naphtha hydrodesulfurized heavy**

Species rat

Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD

Replaces Version: 8 / WORLD

Date created/revised: 03.11.16

Print date: 15.09.16

LC50                                      appr.    100                                      mg/l

Duration of exposure                      4                      h

Remarks      Mist **alkanes, C11-14-**

**iso-**

Species                                      rat

LC50    >              5,6                                      mg/l

Duration of exposure                      =              4                      h

Remarks      Mist                      **naphtha**

**hydrodesulfurized heavy**

LC50    >              5                                      mg/l

Duration of exposure                      4                      h

Remarks                                      Mist

**Skin corrosion/irritation**

Remarks Based on available data, the classification criteria are not met. **Serious eye**

**damage/irritation**

Remarks      Based on available data, the classification criteria are not met. **Sensitization**

Remarks                                      Based on available data, the classification criteria are not met.

**Sensitization (Components)**

**uaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, stearates, salts with bentonite** evaluation      No sensitizing effects known.

**Mutagenicity**

Remarks Based on available data, the classification criteria are not met. **Reproductive toxicity**

Remarks Based on available data, the classification criteria are not met. **Reproduction toxicity**

**(Components)**

**2-ethylhexanoic acid zirconium salt**

Route of exposure                              oral  
evaluation                                      Toxic to Reproduction Category 3

**Carcinogenicity**

Remarks                                      Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity (STOT)**

Remarks                                      The classification criteria are met

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Other information**

No toxicological data are available.

**12. Ecological information**

**12.1. Toxicity**

**General information**

Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD

Date created/revised: 03.11.16

Replaces Version: 8 / WORLD

Print date: 15.09.16

For this subsection there is no ecotoxicological data available on the product as such.

### Fish toxicity (Components)

#### naphtha hydrodesulfurized heavy

Species	Pimephales promelas (fathead minnow)	
LC50	2200	mg/l
Duration of exposure	96	h

#### naphtha hydrodesulfurized heavy

Species	Pimephales promelas (fathead minnow)	
NOEC	2,6	mg/l
Duration of exposure	14	d

#### naphtha hydrodesulfurized heavy

Species	Oncorhynchus mykiss (rainbow trout)	
LC50	16	mg/l
Duration of exposure	96	h

### Daphnia toxicity (Components)

#### naphtha hydrodesulfurized heavy

Species	Chaetogammarus marinus	
EC50	2,6	mg/l
Duration of exposure	96	h

#### naphtha hydrodesulfurized heavy

Species	Daphnia magna (Water flea)	
EC50	4,5	mg/l
Duration of exposure	48	h

#### naphtha hydrodesulfurized heavy

Species	Daphnia magna (Water flea)	
NOEC	2,6	mg/l
Duration of exposure	21	d

#### iso-

Species	Daphnia magna (Water flea)	
EC50	> 1000	mg/l
Duration of exposure	48	h

### Algae toxicity (Components)

#### naphtha hydrodesulfurized heavy

Species	Pseudokirchneriella subcapitata (green algae)	
EC50	3,1	mg/l
Duration of exposure	72	h

## 12.2. Persistence and degradability

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Biodegradability (Components)

**alkanes, C11-14-iso-** evaluation Not readily biodegradable.

#### naphtha hydrodesulfurized heavy

Value	77,05	%
Duration of test evaluation	28	d
	Readily biodegradable.	

Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD  
Replaces Version: 8 / WORLD

Date created/revised: 03.11.16  
Print date: 15.09.16

### 12.3. Bioaccumulative potential

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Partition coefficient: n-octanol/water

Remarks no data available

### 12.4. Mobility in soil

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Mobility in soil

no data available

### 12.5. Results of PBT and vPvB assessment

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

### 12.6. Other adverse effects

#### General information

For this subsection there is no ecotoxicological data available on the product as such. **General information / ecology**

For this subsection there is no ecotoxicological data available on the product as such.

## 13. Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations for the product

EWC waste code 080111 - waste paint and varnish containing organic solvents or other dangerous substances

EWC waste code 200127 - paint, inks, adhesives and resins containing dangerous substances Where possible recycling is preferred to disposal or incineration. Do not allow to enter drains or waterways. **modified product**

EWC waste code 080113 - sludges from paint or varnish containing organic solvents or other dangerous substances

EWC waste code 080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

#### Dried residues

EWC waste code 080112 - waste lacquers and waste paint except those falling under 080111

#### Disposal recommendations for packaging

EWC waste code 150110 - packaging containing residues of or contaminated by dangerous substances Empty remaining contents.

Empty containers should be taken to local recyclers for disposal.

## 14. Transport information Land transport ADR/RID

### 14.1. UN number

UN 1263

### 14.2. UN proper shipping name PAINT

### 14.3. Transport hazard class(es)

Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD  
 Replaces Version: 8 / WORLD

Date created/revised: 03.11.16  
 Print date: 15.09.16

Class 3  
 Label 3

**14.4. Packing group**

Packing group III  
 Special provision 640E  
 Limited Quantity 5I  
 Transport category 3  
 Tunnel restriction code D/E

**Marine transport IMDG/GGVSee**

14.1. UN number UN 1263  
 14.2. UN proper shipping name PAINT  
 14.3. Transport hazard class(es)  
 Class 3  
 14.4. Packing group  
 Packing group III

**Air transport ICAO/IATA**

14.1. UN number UN 1263  
 14.2. UN proper shipping name PAINT  
 14.3. Transport hazard class(es)  
 Class 3  
 14.4. Packing group  
 Packing group III

**15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**VOC**

VOC (EU) 48,2 % 440 g/l

**Non-volatile content**

Value [%] 51,4

**15.2. Chemical safety assessment**

For this substance / mixture a chemical safety assessment was not carried out.

**16. Other information**

**Hazard statements listed in Chapter 3**

EUH066 Repeated exposure may cause skin dryness or cracking.  
 H226 Flammable liquid and vapour.  
 H304 May be fatal if swallowed and enters airways.



Trade name: Whittle Waxes Formula Treatex Hardwax Oil Satin 11001

Version: 9 / WORLD

Date created/revised: 03.11.16

Replaces Version: 8 / WORLD

Print date: 15.09.16

H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H413	May cause long lasting harmful effects to aquatic life.

### CLP categories listed in Chapter 3

Aquatic Chronic 4	Hazardous to the aquatic environment, chronic, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 3	Flammable liquid, Category 3
Repr. 2	Reproductive toxicity, Category 2
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

### Abbreviations

ADR - Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IMDG - International Maritime Code for Dangerous Goods  
IATA - International Air Transport Association  
IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
GHS - Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS - European Inventory of Existing Commercial Chemical Substances  
CAS - Chemical Abstracts Service (division of the American Chemical Society)  
GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)  
LOAEL - Lowest Observed Adverse Effect Level  
LOEL - Lowest Observed Effect Level  
NOAEL - No Observed Adverse Effect Level  
NOEC - No Observed Effect Concentration  
NOEL - No Observed Effect Level  
OECD - Organisation for Economic Cooperation and Development  
VOC - Volatile Organic Compounds  
Changes since the last version are highlighted in the margin (\*\*\*). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.