

# TREATEX WAX POLISH INFORMATION SHEET



## Product Description: Treatex Wax Polish

Treatex Wax Polish is an easy to apply clear polish designed to refresh worn wooden surfaces finished with Treatex Hardwax Oil or Evolution Hardwax Oil.

- **Durable** Treatex Wax Polish forms a durable, water repellent and non-slip finish.
- **Safe** for use on children's' toys contains no pollutants and minimal solvents
- **Easy to apply** can be wiped on using a lint free cloth or buffed on using a slow machine with a white pad.
- **Available in two sheen levels**, Matte, to refresh all surfaces protected with matte Hardwax Oils and regular for all of the higher sheen levels.
- **Fast drying**, it can be applied at night and dry by morning in commercial situations without aggressive odors.
- **Manufactured** on a base of natural sustainable raw materials and forms a durable water repellent and nonslip finish.

### Recommended Tools:

Stirring stick, lint free cloth or white pad on a slow speed buffing machine.

**Clean tools:** with WHITTLE WAXES SPECIAL-THINNER.

### Coverage Rate:

Single application up to 40sqm/L

**Sheen Levels:** Matte, and regular

**Container sizes:** 250ml, 1L and 2.5L

**Drying time:** Allow to dry for at least 3-4hrs – Warmth and ventilation will speed up the drying process. Cold and humidity may slow down the process.

**Storage:** Indefinite in sealed container.

## Floor Preparation:

1. Remove loose dust and dirt using a vacuum cleaner with a soft brush attachment.
2. Clean the surface to be treated with Floor Care Concentrate. For larger commercial surfaces or extremely dirty surfaces clean with Preparation Cleaner, once the surface is completely dry apply Treatex Wax Polish to a small area at a time, either by wiping on a very thin and even coat using a lint free cloth, or by using a white pad under a slow buffing machine ensuring the surface is buffed until there are no swirl marks. Allow to dry for three to four hours.

## Application:

1. Once the surface is completely dry apply Treatex Wax Polish to a small area at a time, either by wiping on a very thin and even coat using a lint free cloth, or by using a white pad under a slow buffing machine ensuring the surface is buffed until there are no swirl marks.
2. Allow to dry for three to four hours.
3. Allow used cloths to dry flat.

**Ingredients:** Oil and Wax combinations on a base of natural, sustainable raw materials including Linseed oil, sunflower oil, Jojoba oil, Beeswax, carnauba wax and candalilla wax.

**GHS:** H413 May cause long lasting harmful effects to aquatic life. P273 Avoid release to the environment. P501.b Dispose of contents/container at an approved waste disposal plant. EUH066 Repeated exposure may cause skin dryness or cracking. Cloths contaminated with this product should be allowed to dry flat to avoid a small chance of self-combustion. This product contains max 525g/l VOC.

**Disclaimer:** Our technical advice in written form is given in good faith and on the basis of experiments, but it is only non-binding advice and does not release you from the obligation to test the products supplied by us as to their suitability for the particular purpose. Application, use and processing of the products outside our direct control are entirely your responsibility. Naturally we guarantee consistent quality of our products corresponding to the original sample. With release of new product information the previous information loses validity.

whittle WAXES P.O. Box 455 Cooroy. QLD 4563 1300 326 929, 1300 ECO WAX